



## Galvanized triple sliding rack for 4-25DK+, 12-25DKF+, 12-50DKR & 25-50IBA

Material no.: 1015837



A rack designed to ensure that the liferaft will immediately drop into the water without assistance. For throw overboard liferafts weighting more than 185 kg sliding ramps are mandatory, in accordance with the SOLAS convention chapter III regulation 16. Pre-drilled foundation holes have a diameter of Ø14.

Sliding rack fits the following liferaft sizes:

- 4DK+
- 6DK+
- 8DK+
- 10DK+
- 12DK+
- 16DK+
- 20DK+
- 25DK+
- 12DKF+
- 16DKF+
- 20DKF+
- 25DKF+
- 12DKR
- 25DKR
- 50DKR
- 25IBA
- 50IBA

Material:	Black steel (S235JR/EN10025/SS400/TIS1479)
Dimensions:	H 151.000 x L 223.000 x W 76.000 cm
Weight:	83 kg
Surface treatment:	Hot dip galvanized class A JF, DS/ISO 1461
Welding:	According to DS/EN 5817 class C
Lashing for fixing of liferaft:	Not included (lashing item number: 1014356 for 4-25DK+, 12-50DKR & 25-50IBA) (lashing item number: 1034948 for 12-25DKF+)